



#### Technical Data

##### Operating voltages:

- 120 VAC, 50/60 Hz
- 240 VAC, 50/60 Hz
- 24 VAC, 50/60 Hz
- 12 VDC
- 24 VDC

##### Rated Power:

3.5 VA

##### Switching:

- SPST
- SPDT

##### Connections:

6.3 x 0.8 mm tab terminals  
(complies with DIN 46244)

##### Switch rating:

- 16 Amps @ 45°C
- 10 Amps @ 55°C

##### Operating Temperature Range:

14°F (-10°C) to 131°F (55°C)

#### Setting Options

- Time of day
- Single day
- Repeat programs for daily recurring switching times
- 1-2-3-4-5 (Monday through Friday)
- 1-2-3-4-5-6 (Monday through Saturday)
- 1-2-3-4-5-6-7 (Monday through Sunday)
- 6-7 (Saturday and Sunday)
- Skip function (→◀▶) for skipping all the switching programs of the next calendar day
- Reset function for clearing the whole switching program

#### Mounting

- Terminal orientation: top, bottom
- Mounting accessories available

#### Approvals

- UL
- CSA Pending
- VDE (@240 VAC)

THIS TIMER IS TYPICAL FOR THE 12VDC TIMER. OTHER TIMERS WITH OTHER VOLTAGES AS DESCRIBED ABOVE HAVE THE SAME SPECS AND ARE THE SAME SIZE. POWER CONSUMPTION: 90-124 MICRO AMPS WITH RELAY NOT ENERGIZED---33-49 mA. ENERGIZED. SOME TIMERS ARE EQUIPPED WITH A SINGLE-POLE-SINGLE-THROW RELAY, AND OTHERS WITH A SINGLE-POLE-DOUBLE-THROW. DO NOT EXCEED THE CONTACT RATING. IF HIGHER AMPS ARE REQUIRED, USE A SECONDARY RELAY OF PROPER CONTACT RATING..